



UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 21-2-2014 Revision date: 31-12-2024 Supersedes version of: 20-9-2021 Version: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : UV resistant varnish gloss
Product code : 980

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Varnish

1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664
Nijendal 36
3972 KC Driebergen Rijsenburg
Nederland
T 0031 343 518 224, F 0031 343 516 342
info@oldholland.com, www.oldholland.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Skin sensitisation, Category 1 H317
Carcinogenicity, Category 1B H350
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause cancer. May cause drowsiness or dizziness. May cause respiratory irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

GHS09

Signal word (CLP)

: Danger

Contains

: reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene); Hydrocarbons, C9, aromatics; cumene

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H350 - May cause cancer.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective gloves, protective clothing.
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
EUH066 - Repeated exposure may cause skin dryness or cracking.
For professional users only.

EUH-statements

Extra phrases

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9, aromatics	CAS-No.: 64742-95-6 REACH-no: 01-2119455851-35	15 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cumene substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 98-82-8 EC-No.: 202-704-5 EC Index-No.: 601-024-00-X	< 10	Flam. Liq. 3, H226 Carc. 1B, H350 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-47-1, 104810-48-2 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-0000015075-76	3 – 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (NL)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	1 – 5	Flam. Liq. 2, H225
methanol substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	0,01 – 1	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 (ATE=0,5 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) STOT SE 1, H370

Specific concentration limits:

Name	Product identifier	Specific concentration limits (Conc. (% w/w))
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	(3 ≤ C < 10) STOT SE 2; H371 (10 ≤ C < 100) STOT SE 1; H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand. Immediately call a POISON CENTER or doctor.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Loosen tight clothing such as a collar, tie, belt or waistband. Immediately call a POISON CENTER/doctor.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Risk of lung oedema.

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing vapours, mist.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure-controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing vapours, mist. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Heat and ignition sources : ignition sources.
- Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ethanol; ethyl alcohol (64-17-5)	
Netherlands - Occupational Exposure Limits	
Local name	Ethanol
TGG-8u (OEL TWA)	260 mg/m ³
	137 ppm
TGG-15min (OEL STEL)	1900 mg/m ³
	1000 ppm
Remark	Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2024

methanol (67-56-1)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Methanol
IOEL TWA	260 mg/m ³
	200 ppm

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

methanol (67-56-1)	
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Netherlands - Occupational Exposure Limits	
Local name	Methanol
TGG-8u (OEL TWA)	133 mg/m ³ 100 ppm
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2024
cumene (98-82-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Phenylpropane (Cumene)
IOEL TWA	50 mg/m ³ 10 ppm
IOEL STEL	250 mg/m ³ 50 ppm
Remark	Skin. During exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Netherlands - Occupational Exposure Limits	
Local name	2-Fenylpropaan (cumeen)
TGG-8u (OEL TWA)	50 mg/m ³ 10 ppm
TGG-15min (OEL STEL)	250 mg/m ³ 50 ppm
Remark	Bij het beoordelen van de blootstelling wordt rekening gehouden met de relevante, door het Wetenschappelijk Comité inzake grenswaarden voor beroepsmatige blootstelling aan chemische agentia (SCOEL) voorgestelde, biologische-monitoringwaarden. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2024

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Breathing equipment.

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses. ISO 16321-1. DIN EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 368; EN 369; EN 467

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0.11		EN ISO 374

Respiratory protection

Respiratory protection:

Wear respiratory protection. EN 143

Respiratory protection			
Device	Filter type	Condition	Standard
Approved respirator	Type P1	Vapour protection, Protection for Liquid particles	EN 143

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	6200 mg/kg
LD50 dermal rabbit	20000 mg/kg
LC50 Inhalation - Rat (Vapours)	95,6 mg/l/4h
Hydrocarbons, C9, aromatics (64742-95-6)	
LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
cumene (98-82-8)	
LD50 oral rat	2260 – 2700 mg/kg
LD50 dermal rabbit	3160 mg/kg
LC50 Inhalation - Rat	10 mg/l mouse

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

methanol (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

Hydrocarbons, C9, aromatics (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

cumene (98-82-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: May be fatal if swallowed and enters airways.

Hydrocarbons, C9, aromatics (64742-95-6)

Viscosity, kinematic	700000 – 1700000 mm ² /s
----------------------	-------------------------------------

11.2. Information on other hazards

Other information

Other information	: Risk of aspiration pneumonia
-------------------	--------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1, 104810-48-2)

LC50 - Fish [1]	2,8 mg/l
-----------------	----------

EC50 - Crustacea [1]	4 mg/l
----------------------	--------

ErC50 algae	> 9 mg/l
-------------	----------

ethanol; ethyl alcohol (64-17-5)

LC50 - Fish [1]	8140 mg/l 48 h
-----------------	----------------

EC50 - Crustacea [1]	9268 – 14221 mg/l 48 h
----------------------	------------------------

EC50 - Crustacea [2]	65 mg/l 72 h
----------------------	--------------

ErC50 algae	1450 mg/l 8 d
-------------	---------------

Hydrocarbons, C9, aromatics (64742-95-6)

LC50 - Fish [1]	9,2 mg/l Oncorhynchus mykiss (Rainbow trout)(OECD 203)
-----------------	--

EC50 - Crustacea [1]	3,2 mg/l Daphnia magna (Water flea)(OECD 202)
----------------------	---

EC50 72h - Algae [1]	2,6 – 2,9 mg/l Pseudokirchneriella subcapitata (OECD 201)
----------------------	---

ErC50 algae	2,6 – 2,9 mg/l
-------------	----------------

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

cumene (98-82-8)	
LC50 - Fish [1]	4,7 mg/l Cyprinodon variegatus (sheepshead minnow)
EC50 - Crustacea [1]	2,14 mg/l Daphnia magna (Water flea)(OECD 202)
EC50 72h - Algae [1]	0,73 – 1,29 mg/l (OECD 201; Desmodesmus subspicatus)

12.2. Persistence and degradability

UV resistant varnish gloss	
Persistence and degradability	No data is available on the degradability of this product.

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1, 104810-48-2)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

ethanol; ethyl alcohol (64-17-5)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	0,9 – 1,67 g O ₂ /g substance
BOD (% of ThOD)	94 % ThOD

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable.

Hydrocarbons, C9, aromatics (64742-95-6)	
Persistence and degradability	Readily biodegradable.

cumene (98-82-8)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Additional information	: Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container. Do not re-use empty containers.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT / PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene)	PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene)	Paint related material (CONTAINS : Hydrocarbons, C9, aromatics ; cumene)	PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene)	PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene)
Transport document description				
UN 1263 PAINT / PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint related material (CONTAINS : Hydrocarbons, C9, aromatics ; cumene), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS : Hydrocarbons, C9, aromatics ; cumene), 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
II	II	II	II	II

UV resistant varnish gloss


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640D, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	: 
Tunnel restriction code (ADR)	: D/E

Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.
MFAG-No	: 127;128

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640D, 650

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

National regulations

Netherlands

ABM category	: Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioaccumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen	: ethanol; ethyl alcohol, cumene are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: ethanol; ethyl alcohol is listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Proper Shipping Name (IATA)	Modified
	Special provisions (RID)	Modified
	Packing instructions (RID)	Modified
	Tank codes for RID tanks (RID)	Modified
	Limited quantities (RID)	Added
	Issue date	Modified
	Revision date	Modified
	Supersedes	Modified
1.2	Main use category	Modified
2.1	Adverse physicochemical, human health and environmental effects	Modified
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified
2.2	Precautionary statements (CLP)	Modified
2.2	Extra phrases	Added
2.2	EUH-statements	Added
2.2	Hazard statements (CLP)	Modified
4.1	First-aid measures for first aider	Added
4.1	First-aid measures after eye contact	Modified
4.1	First-aid measures after ingestion	Modified
4.2	Symptoms/effects after inhalation	Added
4.2	Symptoms/effects after skin contact	Modified
5.1	Suitable extinguishing media	Modified
5.2	Explosion hazard	Added
5.2	Hazardous decomposition products in case of fire	Modified
5.3	Firefighting instructions	Modified

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
5.3	Protection during firefighting	Modified
6.1	Emergency procedures	Modified
6.1	Protective equipment	Added
6.1	General measures	Added
6.1	Emergency procedures	Modified
6.1	Protective equipment	Modified
6.2	Environmental precautions	Modified
6.3	For containment	Modified
6.3	Methods for cleaning up	Modified
6.4	Reference to other sections (8, 13)	Modified
7.1	Precautions for safe handling	Modified
7.1	Hygiene measures	Modified
7.2	Heat and ignition sources	Modified
7.2	Packaging materials	Added
7.2	Technical measures	Modified
7.2	Incompatible products	Removed
7.2	Storage conditions	Modified
8.2	Other information	Modified
8.2	Eye protection	Modified
8.2	Skin and body protection	Modified
8.2	Personal protective equipment	Modified
9	Flammability (solid, gas)	Added
10.1	Reactivity	Modified
10.3	Possibility of hazardous reactions	Modified
10.4	Conditions to avoid	Modified
10.5	Incompatible materials	Removed
12.2	Persistence and degradability	Modified
12.3	Bioaccumulative potential	Removed
13.1	Ecology - waste materials	Removed
13.1	Waste disposal recommendations	Modified
13.1	Regional waste regulation	Added
13.1	Sewage disposal recommendations	Added
13.1	Waste treatment methods	Added
13.1	Additional information	Modified
14.6	Special provisions (ADN)	Modified
15.1	REACH Annex XVII	Modified
16	Other information	Modified

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CAS	CAS (Chemical Abstracts Service) number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	CMR: Carcinogen, Mutagen, Reprotoxisch
	CSA: Chemical Safety Assessment
	CSR: Chemical Safety Report
DNEL	Derived-No Effect Level
	EC50: Median Effective Concentration (required to induce a 50% effect)
	EINECS: European Inventory of Existing Commercial Chemical Substances
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	IATA: International Air Transport Association
	IMDG: International Maritime Code for Dangerous Goods
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
PBT	Persistent Bioaccumulative Toxic
	PNEC: Predicted No Effect Concentration (for environment)
	REACH: Registration, Evaluation and Authorisation of Chemical substances
	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
	SVHC: Substances of Very High Concern
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources

: ECHA (European Chemicals Agency). according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878.

Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1

UV resistant varnish gloss

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Carc. 1B	Carcinogenicity, Category 1B
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H370	Causes damage to organs.
H371	May cause damage to organs.
H411	Toxic to aquatic life with long lasting effects.
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 1B	H350	Calculation method
STOT SE 3	H336	Calculation method
STOT SE 3	H335	Calculation method
Asp. Tox. 1	H304	Expert judgement
Aquatic Chronic 2	H411	Calculation method

The classification complies with : ATP 12

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)858881927 | info@chemprosbv.nl